

PRODUCT SPOTLIGHT

Retractable Block Polymer Casing with Para-Aramid & UHMWPE Webbing

Ref: SF-RFAE-2W

PHYSICAL PARAMETERS

- Quick activating braking mechanism component
- Robust & durable plastic casing
- Para-Aramid and UHMWPE webbing
- Swivel snap hook at attachment end.

LENGTH

- 2 Mtr.



FRONT VIEW

BACK VIEW

WEBBING

- Material: Para-Aramid and UHMWPE
- Minimum Breaking Strength: 15 kN

WEIGHT

- 1.800 kg ± 0.100 kg

USER CAPACITY

- Maximum user weight (Horizontal Use): 140 Kg
- Maximum user weight (Vertical Use): 140 Kg

RELEVANT STANDARD

- EN 360:2023 VG11 RFU 11.060 (Sharp Edge)
- ANSI Z359.14-2021 CLASS 2

VSPL UPDATE

1ST MAY – LABOUR DAY

On 1st May, Labour Day, we at Viraj Syntex rewarded the backbones of the company by hosting a luncheon for all of them. A small gesture of gratitude for the people who drive our progress every day.



VSPL INSIGHT OF THE WEEK

“ Always match webbing strength to real-world load conditions—not just rated capacity.”

Many buyers select webbing based on breaking strength, but in actual use (cargo securing, fall protection, industrial lifting), factors like:

- ✓ dynamic load shifts
- ✓ environmental exposure (UV, moisture, abrasion)
- ✓ repeated stress cycles

can significantly reduce performance.

PRO MOVE: Choose webbing with a safety factor + application-specific testing, not just spec-sheet numbers.

For technical details, samples, or custom requirements, reach out to us:

Email: rishi@virajsyntex.com, ruchi@virajsyntex.com, salesrep@virajsyntex.com

Phone / WhatsApp: +91 9838075687

Website: www.virajsyntex.com